

# OMNIDRIVE

## 56 & 56HZ Frame Three Phase Motors Aluminum Frame TEFC

**New Product**



- Aluminum Construction
- Continuous Duty
- Class 'B' Insulation
- Inverter Duty 10:1 V.T. / 2:1 C.T.
- Ball Bearings
- Removable Bolt-on Feet
- 3 Positions for Feet Allow for F-1, F-2, F-0 Conduit Box Location
- 40°C Ambient
- UL Listed & CSA Approved

Stock #	HP	Volts	Amps.	RPM	"C"	Shaft (Dia.)	Frame
WA631	1/3	208-230 / 460	1.26 - 1.14 / 0.57	3600	12.67"	5/8"	56
WA611	1/3	575	0.46	3600	12.67"	5/8"	56
WA681	1/3	208-230 / 460	1.43 - 1.30 / 0.65	1800	12.67"	5/8"	56
WA661	1/3	575	0.52	1800	12.67"	5/8"	56
WA632	1/2	208-230 / 460	1.82 - 1.64 / 0.82	3600	12.67"	5/8"	56
WA612	1/2	575	0.66	3600	12.67"	5/8"	56
WA682	1/2	208-230 / 460	2.12 - 1.92 / 0.96	1800	12.67"	5/8"	56
WA662	1/2	575	0.77	1800	12.67"	5/8"	56
WA633	3/4	208-230 / 460	2.59 - 2.34 / 1.17	3600	12.67"	5/8"	56
WA613	3/4	575	0.94	3600	12.67"	5/8"	56
WA683	3/4	208-230 / 460	2.94 - 2.66 / 1.33	1800	12.67"	5/8"	56
WA663	3/4	575	1.06	1800	12.67"	5/8"	56
WA634	1	208-230 / 460	3.24 - 2.92 / 1.46	3600	13.66"	5/8"	56H
WA614	1	575	1.17	3600	13.66"	5/8"	56H
WA684	1	208-230 / 460	3.84 - 3.48 / 1.74	1800	13.66"	5/8"	56H
WA664	1	575	1.39	1800	13.66"	5/8"	56H
TA624	1	208-230 / 460	3.24 - 2.92 / 1.46	3600	14.02"	7/8"	56HZ
TA604	1	575	1.17	3600	14.02"	7/8"	56HZ
TA674	1	208-230 / 460	3.84 - 3.48 / 1.74	1800	14.02"	7/8"	56HZ
TA654	1	575	1.39	1800	14.02"	7/8"	56HZ



# OMNIDRIVE

## 56 & 56HZ Frame Three Phase Motors Aluminum Frame TEFC

**New Product**



- Aluminum Construction
- Continuous Duty
- Class 'B' Insulation
- Inverter Duty 10:1 V.T. / 2:1 C.T.
- Ball Bearings
- Removable Bolt-on Feet
- 3 Positions for Feet Allow for F-1, F-2, F-0 Conduit Box Location
- 40°C Ambient
- UL Listed & CSA Approved

Stock #	HP	Volts	Amps.	RPM	"C"	Shaft (Dia.)	Frame
WA635	1-1/2	208-230/460	4.71 - 4.26 / 2.13	3600	13.66"	5/8"	56H
WA615	1-1/2	575	1.70	3600	13.66"	5/8"	56H
WA685	1-1/2	208-230/460	5.28 - 4.78 / 2.39	1800	13.66"	5/8"	56H
WA665	1-1/2	575	1.91	1800	13.66"	5/8"	56H
TA625	1-1/2	208-230/460	4.71 - 4.26 / 2.13	3600	14.02"	7/8"	56HZ
TA605	1-1/2	575	1.70	3600	14.02"	7/8"	56HZ
TA675	1-1/2	208-230/460	5.28 - 4.78 / 2.39	1800	14.02"	7/8"	56HZ
TA655	1-1/2	575	1.91	1800	14.02"	7/8"	56HZ
WA636	2	208-230/460	6.02 - 5.44 / 2.72	3600	13.66"	5/8"	56H
WA616	2	575	2.18	3600	13.66"	5/8"	56H
WA686	2	208-230/460	6.73 - 6.08 / 3.04	1800	13.66"	5/8"	56H
WA666	2	575	2.43	1800	13.66"	5/8"	56H
TA626	2	208-230/460	6.02 - 5.44 / 2.72	3600	14.02"	7/8"	56HZ
TA606	2	575	2.18	3600	14.02"	7/8"	56HZ
TA676	2	208-230/460	6.73 - 6.08 / 3.04	1800	14.02"	7/8"	56HZ
TA656	2	575	2.43	1800	14.02"	7/8"	56HZ
WA637	3	208-230/460	8.76 - 7.92 / 3.96	3600	13.66"	5/8"	56H
WA617	3	575	3.17	3600	13.66"	5/8"	56H
TA627	3	208-230/460	8.70 - 7.96 / 3.96	3600	14.02"	7/8"	56HZ
TA607	3	575	3.17	3600	14.02"	7/8"	56HZ

